

## WT OIL - API: SL/CF MINERAL

### DESCRIPTION:

WT Oil SL/CF is premium quality mineral oil for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is particularly suited to turbocharged engines and perfectly adapted to vehicles equipped with catalysts and using unleaded fuel.

### APPLICATION:

Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles. Four stroke gasoline engines and portable power equipment.

### FEATURES & BENEFITS:

- High viscosity index
- Excellent viscosity stability
- Excellent detergency and dispersancy
- Very high antiwear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SL/CF
- ACEA A3/B3
- RENAULT RN0700/0710 (SAE 15W-40/ 20W-50)
- VW 501.01 / 505 (SAE 15W-40/ 20W-50/20W-60)

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SL/CF (MINERAL)			
			15W-40	20W-50	20W-60	25W-60
SAE Grade			15W-40	20W-50	20W-60	25W-60
Kinematic Viscosity @ 104°F /40°C	D-445	cSt	110.30	180.3	212.2	243.7
Kinematic Viscosity @ 212°F /100°C	D-445	cSt	15	20.2	24.2	24.0
Viscosity Index	D-2270	-	142	131	145	124
SP. Gravity @15°C/ 60°F	D-4052	g/cm3	0.880	0.889	0.888	0.890
Flash Point (min)	D-92	°C	223	236	232	234
Pour Point (max)	D-97	°C	-33	-24	-24	-21
TBN	D-2896	Mg KOH/g	8	8	8	8
CCS, (°C)	D-5293	m.Pa.S	6600 (-35°C)	9500 (-15°C)	9500 (-15°C)	10,000 (-10°C)

Office: 301, Al Moosa Tower 1, Sheikh Zayed Road, Dubai, UAE. +971 4591 3042

info@wealthtayloroil.com | Freezone: Sharjah Media City, Sharjah, UAE.