

WT OIL - API: SJ/CF SYNTHETIC

DESCRIPTION:

WT Oil SJ/CF is a superior quality fully synthetic engine oil formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the buildup of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

APPLICATION:

Recommended for all naturally aspirated, fuel injected, turbocharged and multivalve passenger car engines without particulate filters.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Outstanding wear and friction protection
- Excellent detergency and dispersancy
- Easy start at low temperatures
- Excellent protection against sludge and varnish build-up

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SJ/CF
- ACEA A1/B1 (5W-30)
- ACEA A3/B3 (5W-40)
- ILSAC GF-2
- FORD WSS-M2C-913A/913B (SAE 5W-30)

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SJ/CF (FULLY SYNTHETIC)	
			5W-30	5W-40
SAE Grade			5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D-445	cSt	57.6	87.7
Kinematic Viscosity @ 212°F /100°C	D-445	cSt	10.1	14.5
Viscosity Index	D-2270	-	165	173
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.850	0.874
Flash Point (min)	D-92	°C	224	224
Pour Point (max)	D-97	°C	-42	-42
TBN	D-2896	Mg KOH/g	6	6
CCS, (°C)	D-5293	m.Pa.S	<6600 (-30°C)	<6600 (-30°C)