

## WT OIL - API: SJ/CF SEMI SYNTHETIC

### DESCRIPTION:

WT Oil SJ/CF is semi synthetic engine oil a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.

### APPLICATION:

Suitable for gasoline/diesel/CNG/LNG engines.

### FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Excellent protection against sludge and varnish deposits

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

API SJ/CF

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SJ/CF (SEMI SYNTHETIC)	
			10W-30	10W-40
SAE Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	67.3	90.2
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.6	15
Viscosity Index	D-2270	-	169	176
SP. Gravity @15°C/ 60°F	D-4052	g/cm3	0.852	0.852
Flash Point (min)	D-92	°C	234	234
Pour Point (max)	D-97	°C	-42	-42
TBN	D-2896	Mg KOH/g	6	6
CCS, (°C)	D-5293	m.Pa.S	<6600 (-30°C)	<6600 (-30°C)