

WT OIL - API: SJ/CF MINERAL

DESCRIPTION:

WT Oil SJ/CF mineral engine oil is a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.

APPLICATION:

Suitable for gasoline/diesel/CNG/LNG engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Easy start at low temperatures
- Excellent protection against sludge and varnish deposits

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

API SJ/CF

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SJ/CF (MINERAL)				
			15W-40	20W-50	20W-60	50	40
SAE Grade			15W-40	20W-50	20W-60	50	40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	111.0	170.3	238.6	220.3	150
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	15.23	19.6	25.5	19.5	15.35
Viscosity Index	D-2270	-	140	133	137	101	101
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.885	0.890	0.889	0.898	0.898
Flash Point (min)	D-92	°C	224	236	230	260	260
Pour Point (max)	D-97	°C	-30	-24	-24	-15	-15
TBN	D-2896	Mg KOH/g	6	6	6	6	6
CCS, (°C)	D-5293	m.Pa.S	6750 (-20)	9000 (-15)	9000 (-15)	N/A	N/A