

WT OIL - API: SG/CF

SEMI SYNTHETIC

DESCRIPTION:

WT Oil SG/CF is a semi synthetic oils for gasoline and diesel engines having high ageing resistance, effectively reduces carbon formation and high-temperature lacquer formation. Provides safe lubrication of the engine components. These oils contain low-ash additives which allow to prolong the endurance of the catalyst.

APPLICATION:

Recommended for gasoline and light-duty diesel engines found in passenger cars, agriculture and construction equipment, stationary diesel engines and four-stroke engines. It can be comfortably used in mixed fleet.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Protection against rubber parts
- Good TBN Retention

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

API SG/CF

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SG/CF (SEMI SYNTHETIC)	
			10W-30	10W-40
SAE Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	76.2	100.2
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.9	14.90
Viscosity Index	D-2270	-	152	156
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.869	0.876
Flash Point (min)	D-92	°C	230	230
Pour Point (max)	D-97	°C	-36	-36
TBN	D-2896	Mg KOH/g	6	6
CCS, (°C)	D-5293	m.Pa.S	<6600 (-25°C)	<6700 (-25°C)