

WT OIL - API: SG/CF MINERAL

DESCRIPTION:

WT Oil SG/CF mineral engine oil is a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.

APPLICATION:

Gasoline and light duty diesel engines found in passenger cars. Farm and construction equipment, stationary diesel engines and four stroke engines. It can be comfortably used in mixed fleet.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Protection against rubber parts
- Good TBN Retention

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

API SG/CF

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SG/CF (MINERAL)			
			15W-40	20W-50	20W-60	50
SAE Grade			15W-40	20W-50	20W-60	50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	110.0	170.3	210.0	220.3
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	15.0	19.6	25.5	19.5
Viscosity Index	D-2270	-	139	133	138	100
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.885	0.890	0.889	0.889
Flash Point (min)	D-92	°C	224	236	230	260
Pour Point (max)	D-97	°C	-30	-24	-24	-15
TBN	D-2896	Mg KOH/g	6.5	6.5	6.5	6.5
CCS, (°C)	D-5293	m.Pa.S	<6800 (-20°C)	<9100 (-15°C)	<9300 (-15°C)	-