

WT OIL - API: SF/CD

MINERAL

DESCRIPTION:

WT Oil SF/CD is designed to be used for passenger cars, light trucks as well as farm equipment, especially where single type of oil is preferred. This oil contains inhibitors to combat acids formation, oxidation and foaming. It is formulated with high quality mineral base stock and advance additive system.

APPLICATION:

Gasoline and light duty diesel engines found in passenger cars. Farm and construction equipment, stationary diesel engines and four stroke engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SF/CD
- MIL-L-2104A

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SF/CD (MINERAL)				
			40	50	15W-40	20W-50	20W-60
SAE Grade			40	50	15W-40	20W-50	20W-60
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	150	212.5	110.2	172.95	243.2
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	14.5	19.5	15.2	19.5	25.7
Viscosity Index	D-2270	-	95	105	145	130	136
SP. Gravity @15°C/ 60°F	D-4052	g/cm3	0.898	0.898	0.885	0.89	0.889
Flash Point (min)	D-92	°C	250	254	224	236	232
Pour Point (max)	D-97	°C	-15	-15	-30	-24	-24
TBN	D-2896	Mg KOH/g	6	6	6	6	6
CCS, (°C)	D-5293	m.Pa.S	N/A	N/A	<6800 (-20°C)	<9100 (-15°C)	<9200 (-15°C)