

WT OIL - API: SM/CF SEMI SYNTHETIC

DESCRIPTION:

WT Oil SM/CF is an advanced semi synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.

APPLICATION:

Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles, light truck gasoline engines. Four stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- Enables fast and easy start in extreme temperature conditions
- Particularly recommended for urban driving
- Oil film able to withstand high operating temperatures
- Protects engines against deposits
- Standard drain interval

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SM/CF
- ACEA A3/B3
- VW 501 01 / 505 00
- RN 700, RN 710
- MB 229.3

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SM/CF (SEMI SYNTHETIC)	
			10W-30	10W-40
SAE Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	63.3	100.2
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	10.4	15.1
Viscosity Index	D-2270	-	154	159
SP. Gravity @15°C/ 60°F	D-4052	g/cm3	0.876	0.876
Flash Point (min)	D-92	°C	236	236
Pour Point (max)	D-97	°C	-39	-42
TBN	D-2896	Mg KOH/g	8	8
CCS, (°C)	D-5293	m.Pa.S	<7000 (-25°C)	<6600 (-30°C)