

WT - CVT

CONTINUOUSLY VARIABLE TRANSMISSIONS

DESCRIPTION:

WT CVT is a fully synthetic premium multi-vehicle transmission fluid for passenger cars and vans. It is a well-balanced fluid that provides exceptional metal-to-metal frictional properties to help prevent belt and chain slipping and help extend transmission life. It provides superior performance for outstanding anti-shudder durability and reduced noise, vibration and harshness.

APPLICATION:

Especially recommended for use in push belt and chain-driven continuously variable transmissions of most European, Asian, and American passenger cars and vans.

FEATURES & BENEFITS:

- Exceptional steel on steel friction durability maintains transmission performance
- Good gear wear protection prolongs the performance and life of the transmission
- High shear stability and enhanced anti foaming and air release characteristics maintain effective lubrication
- Superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness
- In elevated heat, guards against the harmful effects of thermal breakdown

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- Audi G 052 180, G 052 516, Multitronic, TL 52 116, TL 52 180, TL 52 516
- BMW 83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A
- CHERY CVT
- CHRYSLER CVTF+4, NS-2
- Citroen AMMIX CVTF DFE, AMMIX CVT Fluid DC, AMMIX CVT, Fluid DFE, CVTF 3320, CVT Fluid DFC, Fluid TC
- Daihatsu 1 490 761, 1 490 763, POWERSHIFT, WSS-M2C200-D2, WSS-M2C200-D3, WSS-M2C200-E1, WSS-M2C936-A
- Dodge 05191184AA, CVTF+4, NS-2
- DS (CAPSA) 9735 EF, Elfmatic CVT, Elfmatic CVT MV
- Fiat Tutela Car CVT N.G
- Ford CVT23, CVT30, MERCON C, WSS-M2C928-A, WSS- M2C933-A, XT-7QCFT
- Honda 1940713, 1940714, CVTF I-Green2, DEX-CVT, HP CVTF 95529854, VT40
- Hyundai CVT-1, Genuine CVTF, SP-CVT 1, SP III (CVT models only)
- Infiniti NS-1, NS-2, NS-3
- JEEP 05191184AA, CVTF+4, NS-2, VTF
- KIA CVT-1, SP-CVT 1, SP III (CVT models only)
- Lexus CVTF 3320, CVT FE, Fluid FE, Fluid TC
- Lifan CVT
- Mazda CVTF 3320, JWS 3320
- Mercedes-Benz A 001 989 46 03, MB 236.20
- MG EM-CVTF
- MINI 83 22 0 136 376, 83 22 0 429 154, COOPER EZL 799 A, EZL 799, ZF CVT V1



WT OIL & GAS

Empowering Energy. Fueling Progress

- Mitsubishi CVTF ECO J4, Dia Queen CVTF-J1 (MMC Diaqueen CVT Fluid J1), Dia Queen CVTF-J4, Dia Queen CVTF-J4+ (MMC Diaqueen CVT Fluid J4 and J4+), MZ313973, SP III (CVT models only)
- Nissan 999MP-NS200P, KTF-1, N-CVT, NS-1, NS-2, NS-2V, NS-3
- OPEL 7-speed CVT, HP CVTF 95529854, VT40
- Peugeot 9735 EF, Elfmatic CVT, Elfmatic CVT MV
- Renault CVT CK/SK/FK, Elfmatic CVT, Elfmatic CVT MV
- Rover EM-CVTF, Unipart Transmatic ATF
- Saturn 22688912, DEX-CVT
- SEAT G 052 180, G 052 516
- Subaru CV30, CVT III Fluid, CVT TR580, CVT TR690, ECVT, High Torque CVT, High Torque CVTF-LV, iCVTF, i-CVTF FG, K0421Y0700, K0425Y0710, K0425Y0711, Linear-tronic chain CVT 3 Fluid, Lineartronic chain CVT and CVT II Fluid, Lineartronic CVTF, Lineartronic High Torque (HT) CVT Fluid, Lineartronic II, NS-2, SOA748V0300
- Suzuki CVTF 3320, CVTF FE, TC
- Toyota 7-speed CVT, HP CVTF 95529854, VT40
- Vauxhall CVTF 4959
- Volvo G 052 180, G 052 516
- VW RDCF01, RDCF02, CVTs
- Zotye 22688912, DEX-CVT

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL CVT
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	34
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	7
Viscosity Index	D-2270	-	173
SP. Gravity @15°C/ 60°F	D-4052	g/cm3	0.845
Flash Point (min)	D-92	°C	220
Pour Point (max)	D-97	°C	-45

Office: 301, Al Moosa Tower 1, Sheikh Zayed Road, Dubai, UAE. +971 4591 3042

info@wealthtayloroil.com | Freezone: Sharjah Media City, Sharjah, UAE.