

WT ATF - DEXRON VI

SYNTHETIC

DESCRIPTION:

WT ATF Dexron VI is a fully synthetic transmission fluid recommended for use in passenger car and light truck automatic transmissions that require a GM Dexron VI or earlier generation fluid. Transmissions include the following Aisin Warner models: AW TF-80SC / SD, AWF21, AF40-6, AM6, AW6A-EI, TF81SC, AF21, GA6F21WA (Mini).

APPLICATION:

All automatic transmissions that require a GM Dexron VI or earlier generation transmission fluid. Hydraulic systems or industrial and mobile equipment operating over a wide temperature range.

FEATURES & BENEFITS:

- Meets stricter performance requirements for new GM 6 Speed automatic transmissions
- Outstanding friction durability for consistent shift performance for the life of the fluid
- Excellent oxidation resistance and thermal stability for long fluid life
- Protects against sludge and varnish formation
- Protects against wear
- Protects against rust and corrosion
- High shear stability
- Excellent low temperature properties
- Good seal compatibility
- Foam resistance

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- | | | |
|---|---------------------------------|----------------|
| • JWS 3309, JWS 3324, T-IV, AW-1, NWS 9638 | • AS 68RC (T IV) | • ZF 5HP 30 |
| • AUDI/VW G-052-162-A1/A2 | • CHRYSLER M1375.4 | • ZFF TE-ML 09 |
| • BMW ETL-7045, 7045E, LA2634, ETL-8072B, 81 22 9 400 275 | • TOYOTA WS | • LT 71141 |
| • GENERAL MOTORS DEXRON II/III/IIH/VI | • VOLVO T-IV | • MERCON LV |
| • HONDA ACURA Z-1 PREMIUM, HONDAMATIC S | • MAZDA ATF M III | |
| • HYUNDAI / KIA SP IV, HYUNDAI SPH-IV | • SUBARU ATF, ATF HP | |
| • JAGUAR ATF 3403 M115, JLM 20238 | • FIAT (ALL VEHICLES) TYPO T-IV | |
| • MITSUBISHI DIAMOND SP-IV | • PEUGEOT ZF 4 HP20 | |
| • MB ZF 4 HP20, 236.1/5/6/7/8/9/236.41 | • PORSCHE ATF 3403-M115 | |
| • ISUZU BESCO ATF II, ATF III | • TOYOTA TYPE T-III, T-IV | |
| • VOITH 55.6635 / VOLVO 97340 | • ZF 5HP 18FL/19FL/24A | |
| • BMW P/N 833227542290 | • CITROEN P/N PR 9980 | |
| • TOYOTA P/N 08886-02305/08886-81015 | • SAAB P/N 93165147 | |

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL DEXRON VI
Kinematic Viscosity @ 104°F / 40°C	D-7042	cSt	29.5
Kinematic Viscosity @ 212°F / 100°C	D-7042	cSt	6.0
Viscosity Index	D-2270	-	155
SP. Gravity @15°C / 60°F	D-4052	g/cm3	0.848
Flash Point (min)	D-92	°C	208
Pour Point (max)	D-97	°C	-48
Viscosity Brookfield @ -40 °C	D-2983	mPa.s (cP)	12500

Office: 301, Al Moosa Tower 1, Sheikh Zayed Road, Dubai, UAE. +971 4591 3042
✉ info@wealthtayloroil.com | Freezone: Sharjah Media City, Sharjah, UAE.