

WT BRAKE FLUID – DOT 3

DESCRIPTION:

WT Brake Fluid DOT 3 is a brake fluid based on polyglycol and is designed for use in hydraulic brake system of commercial vehicles, passenger cars and motorcycles operating under moderate service conditions and requiring a DOT 3 type of fluid. It provides lubrication and system protection. It also is compatible with all seals and metals used in conventional braking systems.

APPLICATION:

It is a high-performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems. Please follow OEM instructions regarding brake fluid type.

FEATURES & BENEFITS:

- Superior oxidative stability
- High boiling point
- Excellent low temperature fluidity ensures trouble free operation
- Effective corrosion inhibitors provide Improved life and reliability of brake system components

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- FMVSS 116 DOT 3
- ISO 4925 (Class 3)
- SAE J1703

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT BRAKE FLUID – DOT 3
DRY ERBP, min	D-1120	°C	> 205
WET ERBP, min	D-1120	°C	> 140
Kinematic Viscosity @ 100C, min	D-445	cSt	> 1.5
Kinematic Viscosity @ -40C	D-445	cSt	< 1500
Ph	D-1287	-	7 to 11.5