

## WT OIL 4T – API: SN SYNTHETIC / SEMI SYNTHETIC

### DESCRIPTION:

WT Oil 4T API SN is a high-performance engine oil formulated specifically to meet the demanding needs of motorcycle engines. It is primarily for on-road, high-performance, 4-cycle sport bikes, however, it may be used in other types of on and off-road 4-cycle motorcycles. It is formulated to help offer outstanding protection in 4-cycle, V-Twin type engines, particularly those which are air cooled and tend to run hotter than other types of engines. Wealth Taylor Oil provides excellent performance in common engine/transmission lubrication system or where the engine lubrication system is separate from the transmission system.

### APPLICATION:

Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

### FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SN
- JASO MA2

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL 4T API SN						
			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50	15W-50
SAE Grade			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50	15W-50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	14.5	12	14.1	25.6	15.3	20.5	19.5
Viscosity Index	D-2270	-	160	145	145	145	120	120	135
SP. Gravity @15°C/60°F	D-4052	g/cm3	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D-92	°C	220	220	220	220	220	220	220
Pour Point (max)	D-97	°C	-39	-36	-36	-36	-24	-24	-33
TBN	D-2896	Mg KOH/g	7	7	7	7	7	7	7
CCS, (°C)	D-5293	m.Pa.S	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-25°C)	<9500 (-15°C)	<9500 (-15°C)	<7000 (-20°C)