

WT OIL 4T – API: SJ

SYNTHETIC / SEMI SYNTHETIC / MINERAL

DESCRIPTION:

WT Oil 4T API SJ is recommended for high-performance 4T motorcycles that delivers high power efficiency and acceleration. It exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions. It is excellent in maintaining high engine power and fuel economy with longer drain interval.

APPLICATION:

Recommended for all scooters and motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SJ
- JASO MA

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL 4T API SJ						
			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50	20W-60
SAE Grade			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50	20W-60
Kinematic Viscosity @ 104°F / 40°C	D-7042	cSt	94.25	76.45	99.5	181.7	122.7	179.5	201.85
Kinematic Viscosity @ 212°F / 100°C	D-7042	cSt	14.8	11.9	14.7	24.9	14.9	19.8	23.5
Viscosity Index	D-2270	-	165	151	155	170	125	128	144
SP. Gravity @ 15°C/60°F	D-4052	g/cm3	0.856	0.867	0.866	0.861	0.890	0.891	0.880
Flash Point (min)	D-92	°C	228	228	226	226	238	236	230
Pour Point (max)	D-97	°C	-42	-39	-39	-36	-24	-24	-24
TBN	D-2896	Mg KOH/g	6	6	6	6	6	6	6
CCS, (°C)	D-5293	m.Pa.S	<6600 (-30)	<7000 (-25)	<7000 (-25)	<7000 (-25)	<9500 (-15)	<9500 (-15)	<9500 (-15)