

WT OIL – SCOOTER

DESCRIPTION:

WT Oil Scooter is formulated from high-quality base stocks and mixed with several additives with a stable thermal detergent system to improve engine cleanliness and durability. This lubricating oil serves to treat and reduce friction as well as provide protection for motorcycle engines. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without a wet clutch.

APPLICATION:

For scooters without wet clutch and where JASO MB specification is required.

FEATURES & BENEFITS:

- Contains Detergent Additive System with Thermal Stable to control deposit levels
- Protects the engine from deposits optimally and the engine life increases longer
- Has a high level of viscosity which makes the engine sound smoother

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SL
- JASO MB

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL SCOOTER	
			10W-30	10W-40
SAE Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	75.35	92.30
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.90	14.0
Viscosity Index	D-2270	-	154	156
SP. Gravity @15°C/60°F	D-4052	g/cm3	0.850	0.851
Flash Point	D-92	°C	230	228
Pour Point	D-97	°C	-36	-36
TBN	D-2896	Mg KOH/g	7.0	7.0