

WT OIL 2T – API: TC

DESCRIPTION:

WT Oil 2T API TC is a lubricant which is designed to provide excellent performance in two stroke engines like motorcycles, scooters and mopeds. Its composition is perfectly compatible with lead-free fuels. This is a high technology product combining a perfect balance of highly refined base stocks and the latest additive's technology. It is specially formulated for use in oil injected as well as premixed gasoline/oil lubricated engines. Its increased performance provides protection against exhaust emissions and engine carbon deposits.

APPLICATION:

It is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended. Product is to be used as per OEM recommended fuel/oil mix ratio. If the specific ratio is not provided, the general recommendation is to use 50:1 fuel/oil mix.

FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke
- Thermal and oxidation stability
- Specially formulated to avoid spark plug fouling
- Perfectly adapted to unleaded fuel
- Protection against pre-ignition problems

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API TC
- JASO FD
- ISO EGD

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	WT OIL 2T
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	60
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	9
Viscosity Index	D-2270	-	127
SP. Gravity @15°C/60°F	D-4052	g/cm3	0.880
Flash Point (min)	D-92	°C	146
Pour Point (max)	D-97	°C	-24
Color	Visual	-	Blue